

Custom**TECH**[®]

FLOORING PREPARATION SYSTEMS

TechLevel[™] 100

Calcium Aluminate Based Self-Leveling Underlayment

- Levels floors from 3/16" to 1-1/2" thick
- Cures fast and develops high early-strength for fast installations
- Crack resistant



A DIVISION OF
CUSTOM[®]
A QUIKRETE[®] COMPANY

TechLevel™ 100

Calcium Aluminate Based Self-Leveling Underlayment

TechLevel™ 100 is a high quality self-leveling underlayment that achieves greater than 4000 psi compressive strength. TechLevel 100 levels floors prior to the installation of tile, resilient flooring, carpet, wood and other floor coverings. This underlayment can be applied up to 1.5" (3.8 cm) thick in one pour and seeks its own level in minutes.

Uses:

Suitable as an Underlayment for:

- Carpet
- Wood, parquet
- Vinyl composition tile (VCT)
- Sheet vinyl flooring
- Laminated flooring
- Vitreous, semi-vitreous or non-vitreous tile
- Ceramic, mosaic, quarry or cement body tile
- Impervious porcelain and glass tile
- Brick and stone veneer
- Cement-based precast terrazzo
- Natural stone tile
- Stone, terrazzo

Suitable Substrates*:

- Absorbent concrete
- Non-absorbent concrete
- Lightweight concrete
- Gypsum-based underlayments
- Existing ceramic tile
- Cement terrazzo
- Epoxy terrazzo
- Exterior grade plywood
- OSB
- Cutback adhesive residue
- Resilient flooring
- Properly prepared steel and aluminum

*Preparation and/or primers may be required to bond to any of these substrates.

Benefits of Product in the Installation:

- Can be applied from 3/16" to 1.5" (3.8 cm) thick in a single pour
- Cures fast and develops high early-strength for quick installation
- Crack resistant

Ordering Information

ITEM CODE	SIZE	PACKAGE
TL10050T	50 lb. (22.68 kg)	Bag

Coverage

Typical square foot coverage per 50 lb. bag (square meter per 22.68 Kg)

Thickness	Square Feet		Thickness	Square Meter	
	Minimum	Maximum		Minimum	Maximum
1/8"	45.98	48.19	3 mm	4.27	4.48
3/16"	30.66	32.13	5 mm	2.85	2.98
1/4"	22.99	24.10	6 mm	2.14	2.24
3/8"	15.33	16.06	9.5 mm	1.42	1.49
1/2"	11.50	12.05	13 mm	1.07	1.12
3/4"	7.66	8.03	19 mm	0.71	0.75
1.0"	5.75	6.02	25 mm	0.53	0.56
1.5"	3.83	4.02	38 mm	0.36	0.37

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.



Warranty: Flooring Installation Systems products are backed by up-to a 25-year warranty. See CustomTechFlooring.com for full warranty information including limitations and exclusions.

©2018 Custom Building Products. All rights reserved. The CUSTOM® and CustomTech® logos, and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit customtechflooring.com for updated technical data sheets and SDS information.

Custom Building Products
800-272-8786
CustomTechFlooring.com
SS197 12/18R



A DIVISION OF

CUSTOM®

A QUIKRETE® COMPANY