

TechLevel HPT

High Performance Calcium Aluminate Based Self-Leveling Topping

- Versatile product, performs as high performance SLU or interior wear surface topping
- Compressive strength > 6,000 psi
- Cures fast; walkable in as little as 2 hours and accepts coatings in 24 hours
- Crack resistant, exceptionally smooth surface





TechLevel[™] HPT

High Performance Calcium Aluminate Based Self-Leveling Topping

TechLevelTM HPT is a High Performance, Self-Leveling Topping designed for fast-track resurfacing and smoothing of interior substrates such as concrete, porous tile and certain non-porous surfaces when properly prepared. TechLevel HPT can be sealed to create a concrete wear surface for commercial, light industrial and residential applications. TechLevel HPT can be installed from 1/4" to 1" in one application. TechLevel HPT is pourable and seeks its own level to produce a smooth, flat, durable surface that hardens quickly and dries fast.

Suitable Substrates:

- Properly prepared concrete
- · Existing ceramic/porcelain tile
- Cementitious and epoxy terazzo

Ordering Information

ITEM CODE	SIZE	PACKAGE
TLHPT50T	50 lb. (22.68 kg)	Bag

Coverage

Typical square foot coverage per 50 lb. bag (square meter per 22.68 Kg)

Square Feet				Square Meter	
Thickness	Minimum	Maximum	Thickness	Minimum	Maximum
1/8"	43.14	45.70	3 mm	4.01	4.25
3/16'	28.76	30.46	5 mm	2.67	2.83
1/4"	21.57	22.85	6 mm	2.00	2.12
3/8"	14.38	15.23	9.5 mm	1.34	1.42
1/2"	10.79	11.42	13 mm	1.00	1.06
3/4"	7.19	7.62	19 mm	0.67	0.71
1.0"	5.39	5.71	25 mm	0.50	0.53

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.



Warranty: Flooring Installation Systems products are backed by up-to a 25-year warranty. See CustomTechFlooring.com for full warranty information including limitations and exclusions.

©2018 Custom Building Products. All rights reserved. The CUSTOM® and CustomTech® logos, and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit customtechflooring, com for updated technical data sheets and SDS information.

