

Custom**TECH**[®]

FLOORING PREPARATION SYSTEMS



TechPatch[™] MP

Calcium Aluminate Based Rapid Setting Multipurpose Patch

- Patches and smooths interior subfloors
- Apply from featheredge to 1/2" (13 mm)
- Install flooring as early as 30 - 90 minutes



A DIVISION OF
CUSTOM[®]
A QUIKRETE[®] COMPANY

TechPatch™ MP Multi-Patch

Calcium Aluminate Based Rapid Setting Multipurpose Patch

TechPatch™ MP is a fast setting, calcium aluminate compound that provides a smooth finish on interior subfloors prior to the installation of a wide variety of floor coverings. Mix with water only to patch, level or skim coat concrete and plywood up to 1/2" (12 mm) thick per application. Install floor coverings in as early as 30 – 90 minutes.

Uses:

Suitable as an Underlayment for:

- Luxury Vinyl Tile (LVT)
- Luxury Vinyl Planks (LVP)
- Carpet flooring
- Vinyl Composition Tile (VCT)
- Sheet vinyl flooring
- Rubber flooring
- Hardwood; laminate and parquet flooring
- Porcelain, ceramic, glass, natural stone and terrazzo

Suitable Substrates*:

- Concrete, masonry and terrazzo
- Gypsum-based underlayment
- Existing resilient flooring
- Cutback adhesive residue
- Approved plywood and OSB
- Moisture mitigation membranes
- Existing ceramic tile & CBU

*Preparation and/or primers may be required to bond to any of these substrates.

Benefits of Product in the Installation:

- Quick-setting formula permits floor covering installation in as little as 30 – 90 minutes
- Smooths the finishes on interior subfloors
- Patches and levels concrete and plywood to 1/2" (13 mm)

Ordering Information

ITEM CODE	SIZE	PACKAGE
TPMP25T	25 lb. (11.34 kg)	Bag

Coverage

Typical square foot coverage per 25 lb. bag (square meter per 11.34 Kg)

Thickness	Square Feet		Thickness	Square Meter	
	Minimum	Maximum		Minimum	Maximum
1/16"	55.30	62.78	1.5 mm	5.14	5.83
1/8"	27.65	31.39	3 mm	2.57	2.92
3/16"	18.43	20.93	5 mm	1.71	1.94
1/4"	13.82	15.70	6.4 mm	1.28	1.46
3/8"	9.22	10.46	10 mm	0.86	0.97
1/2"	6.91	7.85	13 mm	0.64	0.73

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.



Warranty: Flooring Installation Systems products are backed by up-to a 25-year warranty. See CustomTechFlooring.com for full warranty information including limitations and exclusions.

©2018 Custom Building Products. All rights reserved. The CUSTOM® and CustomTech® logos, and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit customtechflooring.com for updated technical data sheets and SDS information.

Custom Building Products
800-272-8786
CustomTechFlooring.com
SS190 12/18R



A DIVISION OF
CUSTOM®
A QUIKRETE® COMPANY