

TechPrime A

Advanced Acrylic Multi-Surface Primer

- Prepares surfaces for application of self-leveling underlayments
- For use over porous and non-porous surfaces
- Solvent-free





TechPrime[™] A

Advanced Acrylic Multi-Surface Primer

TechPrime[™] A is an advanced acrylic primer and sealer that prepares surfaces for the application of an appropriate CustomTech® self-leveling underlayment. It seals porous and non-porous surfaces and improves the bond of the underlayment to the subsurface.

Suitable Substrates:

- Absorbent concrete
- Non-absorbent concrete
- · Lightweight concrete
- · Existing ceramic tile
- Cement terrazzo
- Exterior grade plywood
- · OSB
- Cutback adhesive residue
- VCT
- Approved moisture control membranes

Benefits of Product in the Installation:

- Prepares Surface for Application of Self-Leveling Underlayments
- Use on porous and non-porous substrates; one product for all your primer needs
- Can be used over epoxy-based moisture vapor control products
- Single component no mixing required
- · High solids content enables exceptional bond strengths
- Easy to apply with broom or roller
- Solvent Free; VOC and SCQAMD Compliant

Ordering Information

ITEM CODE	SIZE	PACKAGE
TECHAT1-2	1 gal (3.79 L)	Bottle
TECHAT	3.5 gal (13.24 L)	Pail

Coverage

Typical square foot coverage per gallon (square meter per 3.79L)

Unit Size	Dilution	Minimum Coverage	Maximum Coverage
Non-Porous	Undiluted	400 sq ft (37.16 m²)	600 sq ft (55.74 m²)
Porous	1:3 (primer:water)	600 sq ft (55.74 m²)	1200 sq ft (111.48 m²)

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more sizes, use the material calculator at CustomBuildingProducts.com or contact CUSTOM Technical Services at 800-282-8786.



Warranty: Flooring Installation Systems products are backed by up-to a 25-year warranty. See CustomTechFlooring.com for full warranty information including limitations and exclusions.

©2018 Custom Building Products. All rights reserved. The CUSTOM® and CustomTech® logos, and select product logos are registered trademarks of Custom Building Products, Inc. CUSTOM may make product modifications at any time without notice. Visit customtechflooring, com for updated technical data sheets and SDS information.

